

Residential and Commercial Applications



Splenvue®
TITANIUM

RELIABILITY IS SPLENVUE WITH POWER TO PURIFY WATER

• *Healthy* • *Safety* • *Clean*

Ultraviolet (UV-C rays /253.7 nm) water disinfection system is a unique and rapid method of water disinfection without the use of heat or chemicals to effectively destroys bacteria, virus, mold & algae.

Ultraviolet (UV) light treatment is a widely recognized and proven method of disinfection of water and has several advantages over other disinfection methods such as chlorination, ozonation, etc.... UV light does not add anything to the water, such as undesirable color, odor, taste or flavor, nor does it generate harmful byproducts. It adds only energy in the form of ultraviolet radiation. Also, UV disinfection requires only a fraction of the contact times required by other disinfection methods. It is fast, efficient, effective, economical and environmentally-friendly.



ADVANTAGES

- *Effective* • *Economical* • *Safe*
- *Fast* • *Easy* • *Automatic*
- *Chemical Free*

APPLICATIONS:

Drinking Water / Food Processing / Medical / Industries

DOSAGE IS THE PRODUCT OF INTENSITY & TIME

Dosage = Intensity x Time
= microWatt/cm² x time
= microwatt-seconds per square centimeter (μW-s/cm²)

Note: 1000 μW-s/cm² = 1 mJ/cm² (milli-Joule/cm²)

Titanium™ series



Model#	ST201	ST321	ST411	ST601	ST741	ST951
Flow Rate (30m/Sec based on 99% UVT)	10gpm (2.3 m3/Hr.)	18gpm (4.1 m3/Hr.)	24gpm (5.5 m3/Hr.)	35gpm (7.9 m3/Hr.)	42gpm (9.5 m3/Hr.)	52gpm (11.8 m3/Hr.)
Inlet/Outlet Port	3/4" FNPT with 1" MNPT	3/4" FNPT with 1" MNPT	1" MNPT	1" MNPT	1-1/2" MNPT	1-1/2" MNPT
Reactor	30 cm x 9 cm (12" x 3.5")	52 cm x 9 cm (20.5" x 3.5")	61 cm x 9 cm (24" x 3.5")	80 cm x 9 cm (31.5" x 3.5")	94 cm x 9 cm (37" x 3.5")	115 cm x 9 cm (45.3" x 3.5")
Ballasts Controller	17.6 cm x 7.4 cm x 5.3 cm (6.9" x 2.9" x 2.1")					
Voltage	100 - 250V./50 - 60Hz					
Lamp Watts	30 W	36 W	45 W	65 W	80 W	100 W
Power Consumption	19 W	42 W	52 W	73 W	88 W	110W
Max. Current	1.1 A.					

Control


Lamp Life Time – Countdown
Lamp Replacement Reminder
Total Running Days
Reset Timer
Audible Alarm
Lamp Operation Indicators

Operating Parameters

Max. Operating Pressure 125 psi (8.62 bar)
Ambient Water Temperature 2 - 40° (36 - 104°)
Iron: < 0.3 ppm (0.3 mg/L)
Hardness: < 7 gpg (120 mg/L)
Turbidity: < 1 NTU
UV Transmittance: > 75%


General

4-Log (99.99%) Reduction in bacteria, viruses and protozoan cysts
Electropolished 304SS Reactor Chamber (316SS Available On Request)
Installation: Vertical or Horizontal



Typical Installation

Splenvue®
TITANIUM



Warranty Splenvue® TITANIUM series water disinfection systems carry a TWO year warranty on the stainless steel reactor chamber, a one year warranty on UV lamp, quartz sleeve and other components.



AQUA BEST TECHNOLOGY LIMITED

www.aquabestuv.com sales@aquabestuv.com